



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz... 1.20:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI

MICROWAVE TOWN

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVE TOWN

| | |
|---|------|
| DIRECTION OF VIEW | UNIT |
|   | mm |

| | |
|---------|--------------|
| DRAWN | HaiMin Zhang |
| CHECKED | Gang Cao |
| APPR. | Donald Wu |

1. DRAW ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. HATCH ALL HIDDEN AREAS.
 3. DIMENSIONS ON CROWN CORNERS TO BE CONCENTRIC WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH: Ra

DO NOT SCALE DRAWING

SMA Adapter

DWG NO. K555510P01

OUTLINE DRAWING

SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1

1 2

5 6