



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE&PEI

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVE TOWN

MICROWAVE TOWN

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Haimin Zhang
CHECKED	Gang Cao
APPR.	Donald Wu

1. DRAW ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS.
 3. DIMENSIONS ON CROWN CORNERS TO BE CONCENTRIC WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH:

DO NOT SCALE DRAWING

SMA Adapter

DWG NO. **K555510S01**

OUTLINE DRAWING

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----

1 2

1 2 3 4 5 6

A A

B B

C C

D D