



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.20:1 (Max)
 Power Handling: 0.5W

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

1 2

MicrowaveTown		DIRECTION OF VIEW	UNIT	TITLE
PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN.			mm	2.92mm (Female) Termination
DRAWN	Shaoqing Du	CHECKED	Haimin Zhang	DWG NO.
APPR.	Gang Cao			T360P0Z01
1. EXAMINE ALL DIMENSIONS SPECIFIED. 2. FINISHES AND TOLERANCES ARE AS SHOWN. 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1. 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH:		DO NOT SCALE DRAWING		
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h
				SCALE: 1
				REV. V2.0
				SHEET 1/1

5 6

1 2 3 4 5 6