

Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.25:1 (Max)
 Power Handling: 0.5W

Materials/Finishes:


Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI

MicrowaveTown

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN

DIRECTION OF VIEW	UNIT
 	mm

DRAWN	Shaoping Du
CHECKED	Min Hai Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. FINISH: ALL DIMENSIONS SHALL BE TO CENTER UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CORDS CENTER TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON CORDS CENTER TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH: 

LTR	DESCRIPTION	DATE	APPR.

TITLE
2.4mm (Female) Termination

DWG NO.
T370P0Z01

OUTLINE DRAWING

SIZE: A4_h	SCALE: 1	REV. V2.0	SHEET 1/1
------------	----------	-----------	-----------