



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.25:1 (Max)
 Power Handling: 0.5W

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

1 2

| | | | | | |
|---|-------------|-----------------------------|--------------------------|------------------------|-----------|
| <p>MicrowaveTown</p> <p>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</p> | | <p>DIRECTION OF VIEW</p> | | UNIT | TITLE |
| | | mm | 2.4mm (Male) Termination | | |
| <p>DRAWN: Shaodong Du</p> <p>CHECKED: Min Hai Zhang</p> <p>APPR: Gang Cao</p> | | <p>DWG NO. T371P0Z01</p> | | <p>OUTLINE DRAWING</p> | |
| <p>1. EXAMINE ALL DIMENSIONS. ALL DIMENSIONS SHALL BE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.</p> <p>2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1</p> <p>3. DIMENSIONS ARE AFTER PLATING. SURFACE FINISHES:</p> <p>4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISHES:</p> | | <p>DO NOT SCALE DRAWING</p> | | SIZE: A4_h | SCALE: 1 |
| LTR | DESCRIPTION | DATE | APPR. | REV. | SHEET 1/1 |

5 6