



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

**MicrowaveTown**

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN



UNIT  
mm

TITLE  
N Adapter

DRAWN: HaiMin Zhang  
 CHECKED: Gang Cao  
 APPR.: Donald Wu

DWG NO.  
Z343411Z01

UNLESS OTHERWISE SPECIFIED:  
 1. UNITS: ALL DIMENSIONS ARE IN MILLIMETERS, UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES:  
 DO NOT SCALE DRAWING

OUTLINE DRAWING

SIZE: A4\_h SCALE: 2:1 REV: V1.1 SHEET: 1/1

LTR	DESCRIPTION	DATE	APPR.