



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI

MicrowaveTown

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN

DIRECTION OF VIEW	UNIT
 	mm

DRAWN	Haolin Zhang
CHECKED	Gang Cao
APPR.	Donald Wu

UNLESS OTHERWISE SPECIFIED:
 1. FINISH: ALL DIMENSIONS ARE TO BE CONCENTRIC WITHIN 0.1
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH: 

TITLE
N-TNC Adapter

DWG NO.
Z345400Z01

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING	SIZE	A4_h	SCALE	2:1	REV.	V1.1	SHEET	1/1
1					5				6			