



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI&PTFE

**MICROWAVE TOWN**

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION



UNIT  
mm

TITLE  
N-SMA Adapter

DWG NO.  
Z345510Z01

LTR	DESCRIPTION	DATE	APPR.

DRAWN	Shaoping Du
CHECKED	Haijin Zhang
APPR.	Gang Cao

1. MAKE ALL DIMENSIONS SPECIFIC.  
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. DIMENSIONS ARE AFTER PLATING. SURFACE FINISH: Ra 0.4  
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISH: Ra 0.4

DO NOT SCALE DRAWING	SIZE A4_h	SCALE: 4:1	REV. V1.1	SHEET 1/1
OUTLINE DRAWING				