



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI&PTFE

MICROWAVE TOWN

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION



UNIT
mm

TITLE
N-SMA Adapter

DRAWN: Shaogang Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

DWG NO.
Z345511Z01

LTR	DESCRIPTION	DATE	APPR.

1. REMOVE ALL DIMENSIONS FROM ALL CORNERS, SHOW DIMS. 0.05 IN MIN.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SOURCE FINISHES
 DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V1.1 SHEET: 1/1

OUTLINE DRAWING

1 2

5 6