



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-33GHz
 VSWR: DC-33GHz ... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

Microwavetown
 www.Microwavetown.com

DIRECTION OF VIEW

 DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

TITLE
3.5mm Adapter
 DWG NO.
Z353500Z02

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN.

LTR	DESCRIPTION	DATE	APPR.

UNIT: mm
 TUNING: DIMENSIONS SPECIFIED
 1. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISH: Ra 0.4
 DO NOT SCALE DRAWING

SIZE: A4_h
 SCALE: 4:1
 REV: V2.0
 SHEET: 1/1