



Performance Features:
 Nominal Impedance: 50Ω
 Frequency Range: DC-33GHz
 VSWR: DC-33GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PBT

Microwavetown
 www.Microwavetown.com

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN

DIRECTION OF VIEW

 DRAWN: Min Zhou
 CHECKED: Shaoping Du
 APPR.: Gang Cao

TITLE
 2.92mm-3.5mm Adapter

UNLESS OTHERWISE SPECIFIED:
 1. UNLESS ALL DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN PARENTHESES ARE IN INCHES.
 2. DIMENSIONS ON CROWN CORNERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:
 4. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:

DWG NO.
 Z353600Z02

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
| | | | |
| | | | |
| | | | |

DO NOT SCALE DRAWING
 SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET: 1/1

1 2 3 4 5 6