



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI

Microwavetown
 www.Microwavetown.com

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN.

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Shaogqing Du
CHECKED	Haijin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 A. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS, UNLESS OTHERWISE SPECIFIED.
 B. DIMENSIONS ON DIMENSION LINES TO BE CONCENTRIC WITHIN 0.1
 C. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.

TITLE
 TNCA-TNCA Adapter

DWG NO.
 Z545400Y01

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.	SIZE	A4_h	SCALE	4:1	REV.	V2.0	SHEET	1/1
-----	-------------	------	-------	------	------	-------	-----	------	------	-------	-----