


Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-50GHz

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

M MicrowaveTown Company, LLC
 1283 E. Route 66 Ave.
 Glendora, CA 91741
 Tel: (626)241-9635
 Fax: (626)698-1638
 www.microwavetown.com



UNIT
 mm

TITLE
 2.4mm Connector

P PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN

DRAWN | Shaoqing Du
 CHECKED | Haimin Zhang
 APPR. | Gang Cao

DWG NO.
 D370D47F05-118

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX
 2. LINEARITY TOLERANCES: ± 0.1 ; ANGLE TOLERANCES: $\pm 1^\circ$
 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED \checkmark

OUTLINE DRAWING

| LTR | DESCRIPTION | DATE | APPR. | DO NOT SCALE DRAWING | | | | SIZE | SCALE | REV. | V2.0 | SHEET |
|-----|-------------|------|-------|----------------------|--|--|--|------|-------|------|------|-------|
| | | | | | | | | A4_h | 4: 1 | | | 1/1 |