



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-50GHz  
 VSWR: DC-50GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

**WT** MicrowaveTown Company, LLC  
 1283 E. Route 66 Ave.  
 Glendora, CA 91741  
 Tel: (626)241-9635  
 Fax: (626)698-1638  
 www.microwavetown.com

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN.

DRAWN	DIRECTION OF VIEW	UNIT
Shaoqing Du		mm
CHECKED: HaiJin Zhang		
APPR: Gang Cao		

TITLES  
**2.4mm Connector**  
 DWG NO.  
**D370S20F06**

OUTLINE DRAWING

LTR	DESCR IPTION	DATE	APPR.

1

2

5

6

SCALE: 4:1 REV. V2.0 SHEET 1/1