

Performance Features:


Nominal Impedance: 50Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

M MicrowaveTown Company, LLC
 1283 E. Route 66 Ave.
 Glendora, CA 91741
 Tel:(626)241-9635
 Fax:(626)698-1638
 www.microwavetown.com

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN



UNIT
mm

TITLE

1.85mm Connector

DRAWN Weihaio Pan
 CHECKED Shaoqing Du
 APPR. Gang Cao

DWG NO.

D380S09F05

UNLESS OTHERWISE SPECIFIED:
 1. REMOVE ALL BURS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX
 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1°
 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED

OUTLINE DRAWING

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
| | | | |

DO NOT SCALE DRAWING

| | | | |
|-----------|-----------|-----------|-----------|
| SIZE A4_h | SCALE 1:1 | REV. V2.0 | SHEET 1/1 |
|-----------|-----------|-----------|-----------|