



Performance Features:	
Nominal Impedance: 50Ω Frequency Range: DC-27GHz	
Materials/Finishes:	
Housing: SU303F Polished & Passivated Center Contact: Beryllium Copper Gold Plated Insulators: PTFE&PEI	

M MicrowaveTown Company, LLC
1283 E. Route 66 Ave.
Glendora, CA 91741
Tel: (626)241-9635
Fax: (626)698-1638
www.microwavetown.com

DIRECTION OF VIEW	UNIT	TITLE
	mm	SMA Connector

PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN			
DRAWN	Xin Gong		
CHECKED	Haimin Zhang		
APPR.	Gang Cao		
UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BERRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED			
LTR	DESCRIPTION	DATE	APPR.

DWG NO.	D550P0103F02		
OUTLINE DRAWING			
DO NOT SCALE DRAWING			

SIZE	A4_h	SCALE	4:1	REV.	V2.0	SHEET	1/1
------	------	-------	-----	------	------	-------	-----