



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE

Microwavetown
 www.Microwavetown.com

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN



UNIT
 mm

TITLE
2.92mm Adapter

DRAWN Min Zhou

DWG NO.

CHECKED Shaoping Du

Z3636 10W01

APPR. Gang Cao

1. MAKE ALL DIMENSIONS ALL CORNERS SHARP UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.

OUTLINE DRAWING

LTR DESCRIPTION DATE APPR. DO NOT SCALE DRAWING

SIZE A4_h SCALE: 1 REV. V2.0 SHEET 1/1

1 2

5 6