



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz.... 1.20:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

<b>MicrowaveTown</b> <a href="http://www.MicrowaveTown.com">www.MicrowaveTown.com</a>		DIRECTION OF VIEW	UNIT	TITLE
			mm	1.85mm-2.92mm Adapter
<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>		DRAWN	Shaoqing Du	DWG NO.
		CHECKED	Haimin Zhang	Z363800Z01
		APPR.	Gang Cao	OUTLINE DRAWING
<small>UNLESS OTHERWISE SPECIFIED:          1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX          2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1°          3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1          4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>		<small>DO NOT SCALE DRAWING</small>		
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h   SCALE4: 1   REV. V2.0   SHEET1/1