



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI

MicrowaveTown www.MicrowaveTown.com		DIRECTION OF VIEW 	UNIT mm	TITLE 1.85mm-2.92mm Adapter
<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>		DRAWN Shaoqing Du	DWG NO. Z363810Z01	
		CHECKED Haimin Zhang	OUTLINE DRAWING	
		APPR. Gang Cao		
<small>UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED</small>		DO NOT SCALE DRAWING		
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h
				SCALE 4:1
				REV. V2.0
				SHEET 1/1